Certification Report

BSI-DSZ-CC-0624-2010

for

Samsung S3CC9LC 16-bit RISC Microcontroller for Smart Card, Revision 9 with optional secure RSA 3.7S and ECC 2.4S Libraries including specific IC Dedicated Software

from

Samsung Electronics Co., Ltd.

BSI - Bundesamt für Sicherheit in der Informationstechnik, Postfach 20 03 63, D-53133 Bonn Phone +49 (0)228 99 9582-0, Fax +49 (0)228 9582-5477, Infoline +49 (0)228 99 9582-111

Certification Report V1.0 ZS-01-01-F-326 V4.32





BSI-DSZ-CC-0624-2010

Samsung S3CC9LC 16-bit RISC Microcontroller for Smart Card, Revision 9 with optional secure RSA 3.7S and ECC 2.4S Libraries including specific IC Dedicated Software

from Samsung Electronics Co., Ltd.

PP Conformance: Smartcard IC Platform Protection Profile, Version 1.0,

July 2001, Eurosmart, BSI-PP-0002-2001

Functionality: PP conformant plus product specific extensions

Common Criteria Part 2 extended

Assurance: Common Criteria Part 3 conformant

EAL 5 augmented by

ALC DVS.2, AVA MSU.3 and AVA VLA.4



Common Criteria Recognition Arrangement for components up to EAL 4



The IT product identified in this certificate has been evaluated at an approved evaluation facility using the Common Methodology for IT Security Evaluation, Version 2.3 extended by advice of the Certification Body for components beyond EAL 4 and guidance specific for the technology of the product for conformance to the Common Criteria for IT Security Evaluation (CC), Version 2.3 (ISO/IEC 15408:2005).

This certificate applies only to the specific version and release of the product in its evaluated configuration and in conjunction with the complete Certification Report.

The evaluation has been conducted in accordance with the provisions of the certification scheme of the German Federal Office for Information Security (BSI) and the conclusions of the evaluation facility in the evaluation technical report are consistent with the evidence adduced.

This certificate is not an endorsement of the IT product by the Federal Office for Information Security or any other organisation that recognises or gives effect to this certificate, and no warranty of the IT product by the Federal Office for Information Security or any other organisation that recognises or gives effect to this certificate, is either expressed or implied.

Bonn, 29 January 2010 For the Federal Office for Information Security



SOGIS - MRA

Bernd Kowalski Head of Department L.S.

This page is intentionally left blank.

Preliminary Remarks

Under the BSIG¹ Act, the Federal Office for Information Security (BSI) has the task of issuing certificates for information technology products.

Certification of a product is carried out on the instigation of the vendor or a distributor, hereinafter called the sponsor.

A part of the procedure is the technical examination (evaluation) of the product according to the security criteria published by the BSI or generally recognised security criteria.

The evaluation is normally carried out by an evaluation facility recognised by the BSI or by BSI itself.

The result of the certification procedure is the present Certification Report. This report contains among others the certificate (summarised assessment) and the detailed Certification Results.

The Certification Results contain the technical description of the security functionality of the certified product, the details of the evaluation (strength and weaknesses) and instructions for the user.

-

Act on the Federal Office for Information Security (BSI-Gesetz - BSIG) of 14 August 2009, Bundesgesetzblatt I p. 2821

Contents

A Certification		7
1 Specifications of the Certifica	ation Procedure	7
2 Recognition Agreements		7
2.1 European Recognition of	f ITSEC/CC - Certificates	8
2.2 International Recognition	n of CC - Certificates	8
3 Performance of Evaluation a	and Certification	8
4 Validity of the Certification Re	esult	9
5 Publication		9
B Certification Results		11
1 Executive Summary		12
2 Identification of the TOE		14
3 Security Policy		16
4 Assumptions and Clarification	n of Scope	16
5 Architectural Information		16
6 Documentation		17
7 IT Product Testing		17
8 Evaluated Configuration		18
9 Results of the Evaluation		18
9.1 CC specific results		18
9.2 Results of cryptographic	assessment	19
10 Obligations and Notes for the	he Usage of the TOE	20
11 Security Target		20
12 Definitions		20
12.1 Acronyms		20
12.2 Glossary		22
13 Bibliography		24
C Excerpts from the Criteria		27
D. Annoyos		25

A Certification

1 Specifications of the Certification Procedure

The certification body conducts the procedure according to the criteria laid down in the following:

- BSIG²
- BSI Certification Ordinance³
- BSI Schedule of Costs⁴
- Special decrees issued by the Bundesministerium des Innern (Federal Ministry of the Interior)
- DIN EN 45011 standard
- BSI certification: Procedural Description (BSI 7125) [3]
- Common Criteria for IT Security Evaluation (CC), Version 2.3 (ISO/IEC 15408:2005)⁵
 [1]
- Common Methodology for IT Security Evaluation, Version 2.3 [2]
- BSI certification: Application Notes and Interpretation of the Scheme (AIS) [4]
- Advice from the Certification Body on methodology for assurance components above EAL4 (AIS 34)

2 Recognition Agreements

In order to avoid multiple certification of the same product in different countries a mutual recognition of IT security certificates - as far as such certificates are based on ITSEC or CC - under certain conditions was agreed.

Act on the Federal Office for Information Security (BSI-Gesetz - BSIG) of 14 August 2009, Bundesgesetzblatt I p. 2821

Ordinance on the Procedure for Issuance of a Certificate by the Federal Office for Information Security (BSI-Zertifizierungsverordnung, BSIZertV) of 07 July 1992, Bundesgesetzblatt I p. 1230

Schedule of Cost for Official Procedures of the Bundesamt für Sicherheit in der Informationstechnik (BSI-Kostenverordnung, BSI-KostV) of 03 March 2005, Bundesgesetzblatt I p. 519

Proclamation of the Bundesministerium des Innern of 10 May 2006 in the Bundesanzeiger dated 19 May 2006, p. 3730

2.1 European Recognition of ITSEC/CC - Certificates

The SOGIS-Mutual Recognition Agreement (MRA) for certificates based on ITSEC became initially effective in March 1998.

This agreement on the mutual recognition of IT security certificates was extended in April 1999 to include certificates based on the Common Criteria for the Evaluation Assurance Levels (EAL 1 – EAL 7). This agreement was signed by the national bodies of Finland, France, Germany, Greece, Italy, The Netherlands, Norway, Spain, Sweden and the United Kingdom. The German Federal Office for Information Security (BSI) recognises certificates issued by the national certification bodies of France and United Kingdom, and from The Netherlands since January 2009 within the terms of this agreement.

The SOGIS-MRA logo printed on the certificate indicates that it is recognised under the terms of this agreement.

2.2 International Recognition of CC - Certificates

An arrangement (Common Criteria Recognition Arrangement) on the mutual recognition of certificates based on the CC Evaluation Assurance Levels up to and including EAL 4 has been signed in May 2000 (CCRA). It includes also the recognition of Protection Profiles based on the CC.

As of January 2009 the arrangement has been signed by the national bodies of: Australia, Austria, Canada, Czech Republic, Denmark, Finland, France, Germany, Greece, Hungary, India, Israel, Italy, Japan, Republic of Korea, Malaysia, The Netherlands, New Zealand, Norway, Pakistan, Republic of Singapore, Spain, Sweden, Turkey, United Kingdom, United States of America. The current list of signatory nations and approved certification schemes can be seen on the web site: http://www.commoncriteriaportal.org

The Common Criteria Recognition Arrangement logo printed on the certificate indicates that this certification is recognised under the terms of this agreement.

This evaluation contains the components ADV_IMP.2, ALC_DVS.2, AVA_MSU.3 and AVA_VLA.4 that are not mutually recognised in accordance with the provisions of the CCRA. For mutual recognition the EAL4-components of these assurance families are relevant.

3 Performance of Evaluation and Certification

The certification body monitors each individual evaluation to ensure a uniform procedure, a uniform interpretation of the criteria and uniform ratings.

The product Samsung S3CC9LC 16-bit RISC Microcontroller for Smart Card, Revision 9 with optional secure RSA 3.7S and ECC 2.4S Libraries including specific IC Dedicated Software has undergone the certification procedure at BSI. This is a re-certification based on BSI-DSZ-CC-0501-2008. Specific results from the evaluation process BSI-DSZ-CC-0501-2008 were reused.

The evaluation of the product Samsung S3CC9LC 16-bit RISC Microcontroller for Smart Card, Revision 9 with optional secure RSA 3.7S and ECC 2.4S Libraries including specific IC Dedicated Software was conducted by TÜV IT Informationstechnik GmbH. The

evaluation was completed on 28 January 2010. The TÜV IT Informationstechnik GmbH is an evaluation facility (ITSEF)⁶ recognised by the certification body of BSI.

For this certification procedure the sponsor and applicant is: Samsung Electronics Co., Ltd.

The product was developed by: Samsung Electronics Co., Ltd.

The certification is concluded with the comparability check and the production of this Certification Report. This work was completed by the BSI.

4 Validity of the Certification Result

This Certification Report only applies to the version of the product as indicated. The confirmed assurance package is only valid on the condition that

- all stipulations regarding generation, configuration and operation, as given in the following report, are observed,
- the product is operated in the environment described, where specified in the following report and in the Security Target.

For the meaning of the assurance levels and the confirmed strength of functions, please refer to the excerpts from the criteria at the end of the Certification Report.

The Certificate issued confirms the assurance of the product claimed in the Security Target at the date of certification. As attack methods may evolve over time, the resistance of the certified version of the product against new attack methods can be re-assessed if required and the sponsor applies for the certified product being monitored within the assurance continuity program of the BSI Certification Scheme. It is recommended to perform a re-assessment on a regular basis.

In case of changes to the certified version of the product, the validity can be extended to the new versions and releases, provided the sponsor applies for assurance continuity (i.e. re-certification or maintenance) of the modified product, in accordance with the procedural requirements, and the evaluation does not reveal any security deficiencies.

5 Publication

The product Samsung S3CC9LC 16-bit RISC Microcontroller for Smart Card, Revision 9 with optional secure RSA 3.7S and ECC 2.4S Libraries including specific IC Dedicated Software has been included in the BSI list of the certified products, which is published regularly (see also Internet: https://www.bsi.bund.de) and [5]. Further information can be obtained from BSI-Infoline +49 228 9582-111.

Further copies of this Certification Report can be requested from the developer⁷ of the product. The Certification Report may also be obtained in electronic form at the internet address stated above.

⁶ Information Technology Security Evaluation Facility

Samsung Electronics Co., Ltd. San24, Nongseo-dong Giheung-gu Yongin-City Gyeonggido Korea

This page is intentionally left blank.

B Certification Results

The following results represent a summary of

- the Security Target of the sponsor for the Target of Evaluation,
- the relevant evaluation results from the evaluation facility, and
- complementary notes and stipulations of the certification body.

1 Executive Summary

The Target of Evaluation (TOE) is Samsung S3CC9LC 16-bit RISC Microcontroller for Smart Card, Revision 9 with optional secure RSA 3.7S and ECC 2.4S Libraries including specific IC Dedicated Software. The Target of Evaluation (TOE), the S3CC9LC microcontroller featuring the Tornado™ cryptographic coprocessor, is a smartcard integrated circuit which is composed of a processing unit, security components, contactless and contact based I/O ports, hardware circuit for testing purpose during the manufacturing process and volatile and non-volatile memories (hardware). The TOE also includes any IC Designer/Manufacturer proprietary IC Dedicated Software as long as it physically exists in the smartcard integrated circuit after being delivered by the IC Manufacturer. Such software (also known as IC firmware) is used for testing purpose during the manufacturing process but also provides additional services to facilitate the usage of the hardware and/or to provide additional services, including optional RSA and/or ECC asymmetric cryptography library and an AIS20 compliant random number generation library. The ECC library further includes the functionality of hash computation using SHA1, SHA224 and SHA256 algorithm. The use of these functionalities for keyed hash operations like HMAC or similar security critical operations involving keys and other secrets, is not subject of this TOE and requires specific security improvements and DPA analysis including the operating system, which is not part of this TOE. However, the functionalities of SHA224 and SHA256 computation are intended to be used for signature generation and verification.

The TOE is intended to be used in a range of high security applications like banking and finance applications, communication highways (Internet access and transaction processing), Transport and ticketing applications (access control cards) and Governmental cards (ID cards, health cards, driving licenses). Several security features independently implemented in hardware or controlled by software will be provided to ensure proper operations and the integrity and confidentiality of stored data. This includes measures for memory protection, leakage protection and sensors to allow operations only under specified conditions.

Regarding the RSA and ECC library the user has the possibility to tailor this IC Dedicated Software part of the TOE during the manufacturing process by deselecting the RSA and ECC library. Hence the TOE can be delivered with or without the functionality of the RSA and ECC library what's resulting in four TOE configurations (without RSA and ECC library, with RSA and ECC library, with ECC library only, with RSA library only). This is considered in the Security Target and a corresponding note (indicated by "optional") is added where required. In case the TOE is delivered including the RSA and ECC library, these optional marked parts have to be considered, otherwise these parts can be neglected. If the user decides not to use the RSA and ECC library, they are not delivered to the user and the accompanying "Additional Specific Security Functionality (O.Add-Functions)" Rivest-Shamir-Adleman (RSA) and/or Elliptic Curve Cryptography (ECC) is/are not provided by the TOE. Deselecting the RSA and ECC library means excluding the code implementing functionality, which the user decided not to use. Excluding the code of the deselected functionality has no impact on any other security policy of the TOE, it is exactly equivalent to the situation where the user decides just not to use the functionality. The S3CC9LC single-chip CMOS micro-controller is designed and packaged specifically for "Smart Card" applications.

The main security features of the S3CC9LC integrated circuit are:

 Security sensors or detectors including High and Low Temperature detectors, High and Low Frequency detectors, High and Low Supply Voltage detectors, Supply Voltage Glitch detectors, Light detector and the Passivation Removing Detector

- An Active Shield against physical intrusive attacks
- Dedicated tamper-resistant design based on synthesizable glue logic and secure topology
- Dedicated hardware mechanisms against side-channel attacks such as Internal Variable Clock, Random Waits Generator, Random Current Generator, RAM and EEPROM scrambling mechanisms
- Secure DES Symmetric Cryptography support (part of the evaluation is the triple-DES operation only)
- Secure Tornado[™] co-processor for RSA and ECC Asymmetric Cryptographic Support
- A Deterministic Random Number Generator (DRNG) for AIS20-compliant Random Number Generation

The IC Dedicated Software includes a modular arithmetic library v3.7s for RSA Asymmetric Cryptography support (optional), a modular arithmetic library v2.4s for ECC and SHA support (optional) and a Deterministic Random Number Generator (DRNG) for AIS20-compliant Random Number Generation.

For the detailed information about the Hardware and Software of the Samsung S3CC9LC 16-bit RISC Microcontroller for Smart Card with optional secure RSA 3.7S and ECC 2.4S Library and specific IC Dedicated Software refer to [9], chapter 2.1 to 2.5].

The Security Target [6] is the basis for this certification. It is based on the certified Protection Profile Smartcard IC Platform Protection Profile, Version 1.0, July 2001, Eurosmart, BSI-PP-0002-2001 [10].

The TOE Security Assurance Requirements (SAR) are based entirely on the assurance components defined in Part 3 of the Common Criteria (see part C or [1], Part 3 for details). The TOE meets the Assurance Requirements of the Evaluation Assurance Level EAL 5 augmented by ALC DVS.2, AVA MSU.3 and AVA VLA.4.

The TOE Security Functional Requirements (SFR) relevant for the TOE are outlined in the Security Target [6] resp. [9], chapter 5.1. They are selected from Common Criteria Part 2 and additional SFR are defined in the used Protection Profile. Thus the TOE is CC part 2 extended.

The Security Functional Requirements (SFR) relevant for the IT-Environment of the TOE are outlined in the Security Target Lite [9], chapter 5.2.

The TOE Security Functional Requirements are implemented by the following TOE Security Functions:

TOE Security Function Addressed issue	
SF1	Environmental Security violation recording and reaction
SF2	Access Control
SF3	Non-reversibility of TEST and NORMAL mode

TOE Security Function Addressed issue	
SF4	Hardware countermeasures for unobservability
SF5	Cryptography

Table 1: TOE Security Functions

For more details please refer to the Security Target Lite [9], chapter 6.

The claimed TOE's Strength of Functions " (SOF-) for specific functions as indicated in the Security Target Lite [9], chapter 6 is confirmed. The rating of the Strength of Functions does not include the cryptoalgorithms suitable for encryption and decryption (see BSIG Section 4, Para. 3, Clause 2). For details see chapter 9 of this report.

The assets to be protected by the TOE are defined in the Security Target Lite [9], chapter 3.1. Based on these assets the security environment is defined in terms of Assumptions, Threats and organisational Security Policies. This is outlined in the Security Target Lite [9], chapter 3.1 to 3.4.

This certification covers the following configurations of the TOE:

- Smartcard IC S3CC9LC revision 9 without Crypto Library
- Smartcard IC S3CC9LC revision 9 with RSA Secure Crypto Library V3.7S
- Smartcard IC S3CC9LC revision 9 with ECC Secure Crypto Library V2.4S
- Smartcard IC S3CC9LC revision 9 with RSA Secure Crypto Library V3.7S and ECC Crypto Library V2.4S.

For details refer to chapter 8.

The certification results only apply to the version of the product indicated in the certificate and on the condition that all the stipulations are kept as detailed in this Certification Report. This certificate is not an endorsement of the IT product by the Federal Office for Information Security (BSI) or any other organisation that recognises or gives effect to this certificate, and no warranty of the IT product by BSI or any other organisation that recognises or gives effect to this certificate, is either expressed or implied.

2 Identification of the TOE

The Target of Evaluation (TOE) is called:

Samsung S3CC9LC 16-bit RISC Microcontroller for Smart Card, Revision 9 with optional secure RSA 3.7S and ECC 2.4S Libraries including specific IC Dedicated Software

The following table outlines the TOE deliverables:

No	Type	Identifier	Release	Form of delivery
1	HW	S3CC9LC	Rev. 9	Wafer or module
2	SW	DRNG	V2.0	Object file in electronic form
3	SW	Test ROM Code	V1.0	Included in S3CC9LC Test ROM
4	SW	RSA Secure Crypto Library (optional)	V3.7S	Object file in electronic form
5	SW	ECC Library (optional)	V2.4S	Object file in electronic form
6	DOC	User's manual [16]	V5.0	In electronic form
7	DOC	Security Application Note [12]	V1.7	In electronic form
8	DOC	RSA Application Note [13]	V1.16	In electronic form

No	Type	Identifier	Release	Form of delivery
9	DOC	ECC Application Note [17]	V2.9	In electronic form
10	DOC	DRNG Application Note [14]	V2.0	In electronic form
11	DOC	S3CC9LC/LA/L5 Delivery Specification [15]	Rev. 2.4	In electronic form

Table 2: Deliverables of the TOE

The TOE is identified by S3CC9LC revision 9. Another characteristic of the TOE is the product code. This information is stored in the EEPROM and can be read out by the user of the card via the normal EEPROM read command. It contains the following information at which among others the production line indicator is part of the serial number. Here the hex value "06" at the beginning of the serial number indicates that the TOE is produced in Giheung wafer line 6:

Address	Contents	Data	
80000h – 80001h	Chip status information	Samsung's internal management value	
80002h – 80003h	ROM code number	ROM code number	
80004h – 80005h	Device Type	150C h	
80006h – 8000Fh	Available for customer	All FF h	
80010h – 8001Bh	Serial number	Samsung's internal management value beginning with 06 h	
8001Ch - 8001Dh	IC Fabricator	4250 h	
8001Eh – 8001Fh	IC Fabrication Date	YDDD h (where Y is the last digit of the year and DDD is the number of the day within the year)	
80020h – 80021h	IC Module Fabricator	4252 h	
80022h – 80023h	IC Module Packaging date	YDDD h (where Y is the last digit of the year and DDD is the number of the day within the year)	
80024h – 80027h	IC Serial Number	A proprietary binary number	
80028h – 80029h	IC Batch number	A proprietary binary number	
8002Ah	IC Version	09 h	
8002Bh	Test ROM Code Version	10 h	
8002Ch - 8002Dh	RSA Crypto. Library Version	037C h	
8002Eh	DRNG Library Version	02 h	
8002Fh	ECC Library Version	24 h	
80030h – 8007Fh	Available for customer	All FF h	

Table 3: TOE version information

3 Security Policy

The Security Policy is expressed by the set of Security Functional Requirements and implemented by the TOE. It covers the following issues:

The Security Policy of the TOE is to provide basic Security Functions to be used by the smart card operating system and the smart card application thus providing an overall smart card system security. Therefore, the TOE will implement a symmetric cryptographic block cipher algorithm to ensure the confidentiality of plain text data by encryption and to support secure authentication protocols and it will provide a deterministic random number generator. If the user decides not to use the RSA and/or the ECC crypto libraries the libraries are not delivered to the user. Hence the TOE can be delivered with or without the functionality of the RSA and/or ECC crypto libraries what is resulting in four TOE configurations.

As the TOE is a hardware security platform, the security policy of the TOE is also to provide protection against leakage of information (e.g. to ensure the confidentiality of cryptographic keys during Triple-DES, RSA and ECC cryptographic functions performed by the TOE), against physical probing, against malfunctions, against physical manipulations and against abuse of functionality. Hence the TOE shall

- maintain the integrity and the confidentiality of data stored in the memory of the TOE and
- maintain the integrity, the correct operation and the confidentiality of Security Functions (security mechanisms and associated functions) provided by the TOE.

4 Assumptions and Clarification of Scope

The Assumptions defined in the Security Target and some aspects of Threats and Organisational Security Policies are not covered by the TOE itself. These aspects lead to specific Security Objectives to be fulfilled by the TOE-Environment. The following topics are of relevance: Usage of Hardware Platform, Treatment of User Data, Protection during TOE Development and Production, Protection during Packaging, Finishing and Personalisation. Details can be found in the Security Target [6] and [9], chapter 4.2.

5 Architectural Information

The S3CC9LC 16-bit RISC Microcontroller for Smart Card, Revision 9 with optional secure RSA 3.7S and ECC 2.4S Crypto Library and specific IC Dedicated Software is integrated circuit (IC) providing a platform to a smart card operating system and smart card application software. A top level block diagram and a list of subsystems can be found within the TOE description of the Security Target Lite [9], chapter 2.1. The complete hardware description and the complete instruction set of the TOE is to be found in guidance documents delivered to the customer, see table 2.

The TOE consists of the 19 subsystems (15 hardware / 4 software) as defined in evaluation documentation. For the implementation of the TOE Security Functions basically the components processing unit (CPU) with ROM, EEPROM, RAM, I/O, Deterministic Random Number Generator (DRNG), TORNADO™, Clock, Timer / 16-bit Timer and 20-bit Watchdog, Detectors and Security Control, RESET, Address and Data Bus, DES, Power Control, MPU / Memory Protection Unit, Testrom_code, RSA crypto Library, DRNG Library and ECC Library are used. Security measures for physical protection are realised within the layout of the whole circuitry. For more details refer to [9], chapter 2.1. The Special

Function Registers, the CPU instructions and the various on-chip memories provide the interface to the software using the Security Functions of the TOE.

The subsystem Testrom_code stored on the chip (Test ROM), is used for testing purposes during production only and is completely separated from the use of the embedded software by disabling before TOE delivery.

The TOE includes also functionality to calculate single DES operations, but part of the certification is the Triple-DES operation only.

6 Documentation

The evaluated documentation as outlined in table 2 is being provided with the product to the customer. This documentation contains the required information for secure usage of the TOE in accordance with the Security Target.

Additional obligations and notes for secure usage of the TOE as outlined in chapter 10 of this report have to be followed.

7 IT Product Testing

The tests performed by the developer were divided into six categories:

- technology development tests as the earliest tests to check the technology against the specification and to get the technology parameters used in simulations of the circuitry (this testing is not strictly related to Security Functions);
- 2. tests which are performed in a simulation environment with different tools for the analogue circuitries and for the digital parts of the TOE;
- 3. regression tests of the hardware within a simulation environment based on special software dedicated only for the regression tests;
- 4. regression tests which are performed for the IC Dedicated Test Software and for the IC Dedicated Support Software on emulator versions of the TOE and within a software simulation of the chip in special hardware;
- 5. characterisation and verification tests to release the TOE to production:
 - used to determine the behaviour of the chip with respect to different operating conditions and varied process parameters (often also referred to as characterisation tests)
 - special verification tests for Security Functions which were done with samples of the TOE (referred also as developers security evaluation) and which include also layout tests by automatic means and optical control, in order to verify statements concerning the layout;
- 6. functional production tests, which are done for every chip to check its correct functionality as a last step of the production process (phase 3).

The developer tests cover all Security Functions and all security mechanisms as identified in the functional specification, and in the high and low level designs.

The evaluators were able to repeat the tests of the developer either using the library of programs, tools and prepared chip samples delivered to the evaluator or at the developers site. They performed independent tests to supplement, augment and to verify the tests performed by the developer. The tests of the developer are repeated by sampling, by

repetition of complete regression tests and by software routines developed by the evaluators and computed on samples with evaluation operating system. For the developer tests repeated by the evaluators other test parameters are used and the test equipment was varied. Security features of the TOE realised by specific design and layout measures were checked by the evaluators during layout inspections both in design data and on the final product.

The evaluation provides evidence that the actual version of the TOE provides the Security Functions as specified by the developer. The test results confirm the correct implementation of the TOE Security Functions.

For penetration testing the evaluators took all Security Functions into consideration. Intensive penetration testing was planned based on the analysis results and performed for the underlying mechanisms of Security Functions using bespoke equipment and expert know how. The penetration tests considered both the physical tampering of the TOE and attacks which do not modify the TOE physically.

8 Evaluated Configuration

In the broadest sense, the production of the mask sets for the chip production may be looked upon as the procedure for the system generation. The TOE can be delivered in four configurations:

- Smartcard IC S3CC9LC revision 9 without Crypto Library
- Smartcard IC S3CC9LC revision 9 with RSA Secure Crypto Library V3.7S
- Smartcard IC S3CC9LC revision 9 with ECC Secure Crypto Library V2.4S
- Smartcard IC S3CC9LC revision 9 with RSA Secure Crypto Library V3.7S and ECC Crypto Library V2.4S.

No further generation of TOE takes place after delivery to the customer. After delivery the TOE only features one fixed configuration (normal mode), which cannot be altered by the user. The TOE was tested in this configuration. All the evaluation and certification results therefore are only effective for this version of the TOE. For all evaluation activities performed in test mode, there was a rationale why the results are valid for the normal mode, too.

Every information of how to use the TOE and its Security Functions by the software is provided within the user documentation.

9 Results of the Evaluation

9.1 CC specific results

The Evaluation Technical Report (ETR) [7] was provided by the ITSEF according to the Common Criteria [1], the Methodology [2], the requirements of the Scheme [3] and all interpretations and guidelines of the Scheme (AIS) [4] as relevant for the TOE.

The Evaluation Methodology CEM [2] was used for those components up to EAL4 extended by advice of the Certification Body for components beyond EAL 4 and guidance specific for the technology of the product [4] (AIS 34).

The following guidance specific for the technology was used:

The Application of CC to Integrated Circuits

- The Application of Attack Potential to Smartcards
- Functionality classes and evaluation methodology of deterministic random number generators

(see [4], AIS 20, AIS 25, AIS 26) were used.

As a result of the evaluation the verdict PASS is confirmed for the following assurance components:

- All components of the class ASE
- All components of the EAL 5 package as defined in the CC (see also part C of this report)
- The components ALC_DVS.2, AVA_MSU.3 and AVA_VLA.4 augmented for this TOE evaluation.
- All components claimed in the Security Target [6] and [9], chapter 6 and defined in the CC (see also part C of this report)

As the evaluation work performed for this certification procedure was carried out as a reevaluation based on the certificate BSI-DSZ-CC-0501-2008, re-use of specific evaluation tasks was possible.

The evaluation has confirmed:

• PP Conformance: Smartcard IC Platform Protection Profile, Version 1.0,

July 2001, Eurosmart, BSI-PP-0002-2001 [10]

• for the Functionality: PP conformant plus product specific extensions

Common Criteria Part 2 extended

• for the Assurance: Common Criteria Part 3 conformant

EAL 5 augmented by

ALC DVS.2, AVA MSU.3 and AVA VLA.4

The following TOE Security Functions fulfil the claimed Strength of Function :

SF3 – Non-reversibility of TEST and NORMAL modes

SF5 – Deterministic Random Number Generator (part of SF5)

The cryptographic algorithm of Triple-DES can also be analysed with permutational or probabilistic methods but that was not part of this certification.

In order to assess the Strength of Function the scheme interpretations AIS 20, AIS 25 and AIS 26 (see [4]) were used. For specific evaluation results regarding the development and production environment see annex B in part D of this report.

The results of the evaluation are only applicable to the TOE as defined in chapter 2 and the configuration as outlined in chapter 8 above.

9.2 Results of cryptographic assessment

The rating of the Strength of Functions does not include the cryptoalgorithms suitable for encryption and decryption (see BSIG Section 4, Para. 3, Clause 2). The following cryptographic algorithms are used by the TOE to enforce its security policy:

 hash functions: SHA1, SHA224 and SHA256, the use of these functionalities for keyed hash operations like HMAC or similar security critical operations involving keys and other secrets, is not subject of this TOE and requires specific security improvements and DPA analysis including the operating system, which is not part of this TOE.

However, the functionalities of SHA224 and SHA256 computation are intended to be used for signature generation and verification.

algorithms for the encryption and decryption Triple-DES, RSA and ECC

This holds for the following security functions: SF5

The strength of the cryptographic algorithms was not rated in the course of this evaluation (see BSIG Section 9, Para. 4, Clause 2). But Cryptographic functions with a security level of 80 bits or lower can no longer be regarded as secure against attacks with high attack potential without considering the application context. Therefore for these functions it shall be checked whether the related crypto operations are appropriate for the intended system. Some further hints and guidelines can be derived from the 'Technische Richtlinie BSI TR-02102' (www.bsi.bund.de).

The Cryptographic Functionality 2-key Triple DES (2TDES) provided by the TOE achieves a security level of maximum 80 Bits (in general context).

10 Obligations and Notes for the Usage of the TOE

The operational documents as outlined in table 2 contain necessary information about the usage of the TOE and all security hints therein have to be considered. In addition, the following aspects need to be fulfilled when using the TOE:

The TOE is delivered to Card Manufacturer and the Smartcard Embedded Software Developer. The actual end user obtains the TOE from the operating system producer together with the application which runs on the TOE. The Smartcard Embedded Software Developer receives all necessary requirements to develop his software in form of the delivered documentation.

• All security hints described in [16] and the delivered documents[12], [13], [17], [14] have to be considered.

The Card Manufacturer receives all necessary requirements to develop his software in form of the delivered documentation.

All security hints described in [15] have to be considered.

11 Security Target

For the purpose of publishing, the Security Target [9] of the Target of Evaluation (TOE) is provided within a separate document as Annex A of this report. It is a sanitised version of the complete Security Target [6] used for the evaluation performed. Sanitisation was performed according to the rules as outlined in the relevant CCRA policy (see AIS 35 [4])

12 Definitions

12.1 Acronyms

AES Advanced Encryption Standard

BSI Bundesamt für Sicherheit in der Informationstechnik / Federal Office for Information Security, Bonn, Germany

BSIG BSI-Errichtungsgesetz, Act setting up the Federal Office for Information Security

CBC Cipher Block Chaining

CC Common Criteria for IT Security Evaluation

CRC Cyclic Redundancy Check
CPU Central Processing Unit

CMOS Complimentary Metal Oxide Semiconductor

DES Data Encryption Standard; symmetric block cipher algorithm

DPA Differential Power Analysis

DRNG Deterministic Random Number Generator

EAL Evaluation Assurance Level

ECB Electronic Code Book

ECC Elliptic Curve Cryptography

EEPROM Electrically Erasable Programmable Read Only Memory

EMA Electro Magnetic Analysis

ETR Evaluation Technical Report

HMAC Hash-based Message Authentication Code

IC Integrated Circuit

I/O Input/Output

IT Information Technology

ITSEF Information Technology Security Evaluation Facility

MPU Memory Protection Unit

PP Protection Profile

RAM Random Access Memory
RNG Random Number Generator

ROM Read Only Memory

RSA Rivest, Shamir, Adleman – a public key encryption algorithm

SF Security Function

SFP Security Function Policy

SFR Security Functional Requirement

SOF Strength of Function

ST Security Target

TOE Target of Evaluation

Triple-DES Symmetric block cipher algorithm based on the DES

TSC TSF Scope of Control
TSF TOE Security Functions

TSP TOE Security Policy

TSS TOE Summary Specification

UART Universal Asynchronous Receiver and Transmitter

USB Universal Serial Bus

12.2 Glossary

Augmentation - The addition of one or more assurance component(s) from CC Part 3 to an EAL or assurance package.

Extension - The addition to an ST or PP of functional requirements not contained in part 2 and/or assurance requirements not contained in part 3 of the CC.

Formal - Expressed in a restricted syntax language with defined semantics based on well-established mathematical concepts.

Informal - Expressed in natural language.

Object - An entity within the TSC that contains or receives information and upon which subjects perform operations.

Protection Profile - An implementation-independent set of security requirements for a category of TOEs that meet specific consumer needs.

Security Function - A part or parts of the TOE that have to be relied upon for enforcing a closely related subset of the rules from the TSP.

Security Target - A set of security requirements and specifications to be used as the basis for evaluation of an identified TOE.

Semiformal - Expressed in a restricted syntax language with defined semantics.

Strength of Function - A qualification of a TOE security function expressing the minimum efforts assumed necessary to defeat its expected security behaviour by directly attacking its underlying security mechanisms.

SOF-basic - A level of the TOE strength of function where analysis shows that the function provides adequate protection against casual breach of TOE security by attackers possessing a low attack potential.

SOF-medium - A level of the TOE strength of function where analysis shows that the function provides adequate protection against straightforward or intentional breach of TOE security by attackers possessing a moderate attack potential.

SOF-high - A level of the TOE strength of function where analysis shows that the function provides adequate protection against deliberately planned or organised breach of TOE security by attackers possessing a high attack potential.

Subject - An entity within the TSC that causes operations to be performed.

Target of Evaluation - An IT product or system and its associated administrator and user guidance documentation that is the subject of an evaluation.

TOE Security Functions - A set consisting of all hardware, software, and firmware of the TOE that must be relied upon for the correct enforcement of the TSP.

TOE Security Policy - A set of rules that regulate how assets are managed, protected and distributed within a TOE.

TSF Scope of Control - The set of interactions that can occur with or within a TOE and are subject to the rules of the TSP.

13 Bibliography

[1] Common Criteria for Information Technology Security Evaluation, Version 2.3, August 2005

- [2] Common Methodology for Information Technology Security Evaluation (CEM), Evaluation Methodology, Version 2.3, August 2005
- [3] BSI certification: Procedural Description (BSI 7125)
- [4] Application Notes and Interpretations of the Scheme (AIS) as relevant for the TOE.8
- [5] German IT Security Certificates (BSI 7148, BSI 7149), periodically updated list published also on the BSI Website
- [6] Security Target of Samsung S3CC9LC 16-bit Secure RISC Microcontroller for Smart Card with optional secure RSA and ECC Library including specific IC Dedicated Software, Version 2.1, 20th November 2009 Samsung Electronics (confidential document)
- [7] Evaluation Technical Report Summary (ETR SUMMARY), 8105621102 / BSI-DSZ-CC-0624, S3CC9LC, Version 2, 2010-01-28, TÜViT (confidential document)
- [8] Configuration Management Documentation (Class ACM_AUT/CAP/SCP) Project Cheyenne II Site, version 1.6, 2009-08-05, Samsung (confidential document)
- [9] Security Target Lite of S3CC9LC 16-bit RISC Microcontroller for Smart Cards Project Cheyenne II ECC, version 1.4, 2009-12-15, Samsung
- [10] Smart card IC Platform Protection Profile, Version 1.0, July 2001, BSI registration ID: BSI-PP-0002-2001, developed by Atmel Smart Card ICs, Hitachi Ltd., Infineon Technologies AG, Philips Semiconductors
- [11] ETR for Composite Evaluation (ETR-COMP), 8104953923 / BSI-DSZ-CC-0624, S3CC9LC, Version 2, 2010-01-28, TÜViT (confidential document)

8 specifically

 AIS 20, Version 1, 2 December 1999, Funktionalitätsklassen und Evaluationsmethodologie für deterministische Zufallszahlengeneratoren

- AIS 25, Version 6, 7 September 2009, Anwendung der CC auf Integrierte Schaltungen including JIL Document and CC Supporting Document
- AIS 26, Version 6, 7 May 2009, Evaluationsmethodologie für in Hardware integrierte Schaltungen including JIL Document and CC Supporting Document
- AIS 31, Version 1, 25 September 2001 Funktionalitätsklassen und Evaluationsmethodologie für physikalische Zufallszahlengeneratoren
- AIS 32, Version 1, 2 July 2001, Übernahme international abgestimmter CC-Interpretationen ins deutsche Zertifizierungsschema.
- AIS 34, Version 2, 24 October 2008, Evaluation Methodology for CC Assurance Classes for EAL5+
- AIS 35, Version 2.0, 12 November 2007, Öffentliche Fassung des Security Targets (ST-Lite) including JIL Document and CC Supporting Document and CCRA policies
- AIS 36, Version 2, 12 November 2007, Kompositionsevaluierung including JIL Document and CC Supporting Document
- AIS 38, Version 2.0, 28 September 2007, Reuse of evaluation results

[12] Security Application Note, S3CC9LC family, version 1.7, 2009-12-15, Samsung

- [13] Application Note RSA Crypto Library with Tornado™ V3.7S, version 1.16, 2009-04-30, Samsung
- [14] Application Note DRNG Software Library v2.0, version 2.0, 2006-12-13, Samsung
- [15] S3CC9LC/LA/L5 Chip Delivery Specification, version 2.4, 2009-12, Samsung
- [16] S3CC9GC/GW/LC 16-Bit CMOS Microcontroller for Smart Card User's manual, version 5.0, May 2007, Samsung
- [17] Technical Report: PKA-2 EC Library API Manual (TN PKA2_ECC_APIManual_v29), version 2.9, 2009-08-18, Samsung

This page is intentionally left blank.

C Excerpts from the Criteria

CC Part1:

Conformance results (chapter 7.4)

"The conformance result indicates the source of the collection of requirements that is met by a TOE or PP that passes its evaluation. This conformance result is presented with respect to CC Part 2 (functional requirements), CC Part 3 (assurance requirements) and, if applicable, to a pre-defined set of requirements (e.g., EAL, Protection Profile).

The conformance result consists of one of the following:

- **CC Part 2 conformant** A PP or TOE is CC Part 2 conformant if the functional requirements are based only upon functional components in CC Part 2.
- CC Part 2 extended A PP or TOE is CC Part 2 extended if the functional requirements include functional components not in CC Part 2.

plus one of the following:

- CC Part 3 conformant A PP or TOE is CC Part 3 conformant if the assurance requirements are based only upon assurance components in CC Part 3.
- CC Part 3 extended A PP or TOE is CC Part 3 extended if the assurance requirements include assurance requirements not in CC Part 3.

Additionally, the conformance result may include a statement made with respect to sets of defined requirements, in which case it consists of one of the following:

- Package name Conformant A PP or TOE is conformant to a pre-defined named functional and/or assurance package (e.g. EAL) if the requirements (functions or assurance) include all components in the packages listed as part of the conformance result.
- Package name Augmented A PP or TOE is an augmentation of a pre-defined named functional and/or assurance package (e.g. EAL) if the requirements (functions or assurance) are a proper superset of all components in the packages listed as part of the conformance result.

Finally, the conformance result may also include a statement made with respect to Protection Profiles, in which case it includes the following:

 PP Conformant - A TOE meets specific PP(s), which are listed as part of the conformance result."

CC Part 3:

Protection Profile criteria overview (chapter 8.2)

"The goal of a PP evaluation is to demonstrate that the PP is complete, consistent, technically sound, and hence suitable for use as a statement of requirements for one or more evaluatable TOEs. Such a PP may be eligible for inclusion within a PP registry.

Assurance Class	Assurance Family
	TOE description (APE_DES)
	Security environment (APE_ENV)
Class APE: Protection Profile evaluation	PP introduction (APE_INT)
	Security objectives (APE_OBJ)
	IT security requirements (APE_REQ)
	Explicitly stated IT security requirements (APE_SRE)

Table 3 - Protection Profile families - CC extended requirements"

Security Target criteria overview (Chapter 8.3)

"The goal of an ST evaluation is to demonstrate that the ST is complete, consistent, technically sound, and hence suitable for use as the basis for the corresponding TOE evaluation.

Assurance Class	Assurance Family
	TOE description (ASE_DES)
	Security environment (ASE_ENV)
Class ASE: Security Target evaluation	ST introduction (ASE_INT)
	Security objectives (ASE_OBJ)
	PP claims (ASE_PPC)
	IT security requirements (ASE_REQ)
	Explicitly stated IT security requirements (ASE_SRE)
	TOE summary specification (ASE_TSS)

Table 5 - Security Target families - CC extended requirements "

Assurance categorisation (chapter 7.5)

"The assurance classes, families, and the abbreviation for each family are shown in Table 1.

Assurance Class	Assurance Family
	CM automation (ACM_AUT)
ACM: Configuration management	CM capabilities (ACM_CAP)
	CM scope (ACM_SCP)
ADO: Delivery and operation	Delivery (ADO_DEL)
	Installation, generation and start-up (ADO_IGS)
	Functional specification (ADV_FSP)
	High-level design (ADV_HLD)
ADV: Development	Implementation representation (ADV_IMP)
	TSF internals (ADV_INT)
	Low-level design (ADV_LLD)
	Representation correspondence (ADV_RCR)
	Security policy modeling (ADV_SPM)
AGD: Guidance documents	Administrator guidance (AGD_ADM)
	User guidance (AGD_USR)
	Development security (ALC_DVS)
ALC: Life cycle support	Flaw remediation (ALC_FLR)
	Life cycle definition (ALC_LCD)
	Tools and techniques (ALC_TAT)
	Coverage (ATE_COV)
ATE: Tests	Depth (ATE_DPT)
	Functional tests (ATE_FUN)
	Independent testing (ATE_IND)
	Covert channel analysis (AVA_CCA)
AVA: Vulnerability assessment	Misuse (AVA_MSU)
	Strength of TOE security functions (AVA_SOF)
	Vulnerability analysis (AVA_VLA)

Table 1: Assurance family breakdown and mapping"

Evaluation assurance levels (chapter 11)

"The Evaluation Assurance Levels (EALs) provide an increasing scale that balances the level of assurance obtained with the cost and feasibility of acquiring that degree of assurance. The CC approach identifies the separate concepts of assurance in a TOE at the end of the evaluation, and of maintenance of that assurance during the operational use of the TOE.

It is important to note that not all families and components from CC Part 3 are included in the EALs. This is not to say that these do not provide meaningful and desirable assurances. Instead, it is expected that these families and components will be considered for augmentation of an EAL in those PPs and STs for which they provide utility."

Evaluation assurance level (EAL) overview (chapter 11.1)

"Table 6 represents a summary of the EALs. The columns represent a hierarchically ordered set of EALs, while the rows represent assurance families. Each number in the resulting matrix identifies a specific assurance component where applicable.

As outlined in the next section, seven hierarchically ordered evaluation assurance levels are defined in the CC for the rating of a TOE's assurance. They are hierarchically ordered inasmuch as each EAL represents more assurance than all lower EALs. The increase in assurance from EAL to EAL is accomplished by substitution of a hierarchically higher assurance component from the same assurance family (i.e. increasing rigour, scope, and/or depth) and from the addition of assurance components from other assurance families (i.e. adding new requirements).

These EALs consist of an appropriate combination of assurance components as described in chapter 7 of this Part 3. More precisely, each EAL includes no more than one component of each assurance family and all assurance dependencies of every component are addressed.

While the EALs are defined in the CC, it is possible to represent other combinations of assurance. Specifically, the notion of "augmentation" allows the addition of assurance components (from assurance families not already included in the EAL) or the substitution of assurance components (with another hierarchically higher assurance component in the same assurance family) to an EAL. Of the assurance constructs defined in the CC, only EALs may be augmented. The notion of an "EAL minus a constituent assurance component" is not recognised by the standard as a valid claim. Augmentation carries with it the obligation on the part of the claimant to justify the utility and added value of the added assurance component to the EAL. An EAL may also be extended with explicitly stated assurance requirements.

Assurance Class	Assurance Family	Assura Evalua		urance		onents		by
		EAL1	EAL2	EAL3	EAL4	EAL5	EAL6	EAL7
Configuration	ACM_AUT				1	1	2	2
management	ACM_CAP	1	2	3	4	4	5	5
	ACM_SCP			1	2	3	3	3
Delivery and	ADO_DEL		1	1	2	2	2	3
operation	ADO_IGS	1	1	1	1	1	1	1
Development	ADV_FSP	1	1	1	2	3	3	4
	ADV_HLD		1	2	2	3	4	5
	ADV_IMP				1	2	3	3
	ADV_INT					1	2	3
	ADV_LLD				1	1	2	2
	ADV_RCR	1	1	1	1	2	2	3
	ADV_SPM				1	3	3	3
Guidance documents	AGD_ADM	1	1	1	1	1	1	1
	AGD_USR	1	1	1	1	1	1	1
	ALC_DVS			1	1	1	2	2
support	ALC_FLR							
	ALC_LCD				1	2	2	3
	ALC_TAT				1	2	3	3
Tests	ATE_COV		1	2	2	2	3	3
	ATE_DPT			1	1	2	2	3
	ATE_FUN		1	1	1	1	2	2
	ATE_IND	1	2	2	2	2	2	3
Vulnerability assessment	AVA_CCA					1	2	2
	AVA_MSU			1	2	2	3	3
	AVA_SOF		1	1	1	1	1	1
	AVA_VLA		1	1	2	3	4	4

Table 6: Evaluation assurance level summary"

Evaluation assurance level 1 (EAL1) - functionally tested (chapter 11.3)

"Objectives

EAL1 is applicable where some confidence in correct operation is required, but the threats to security are not viewed as serious. It will be of value where independent assurance is required to support the contention that due care has been exercised with respect to the protection of personal or similar information.

EAL1 provides an evaluation of the TOE as made available to the customer, including independent testing against a specification, and an examination of the guidance documentation provided. It is intended that an EAL1 evaluation could be successfully conducted without assistance from the developer of the TOE, and for minimal outlay.

An evaluation at this level should provide evidence that the TOE functions in a manner consistent with its documentation, and that it provides useful protection against identified threats."

Evaluation assurance level 2 (EAL2) - structurally tested (chapter 11.4)

"Objectives

EAL2 requires the co-operation of the developer in terms of the delivery of design information and test results, but should not demand more effort on the part of the developer than is consistent with good commercial practice. As such it should not require a substantially increased investment of cost or time.

EAL2 is therefore applicable in those circumstances where developers or users require a low to moderate level of independently assured security in the absence of ready availability of the complete development record. Such a situation may arise when securing legacy systems, or where access to the developer may be limited."

Evaluation assurance level 3 (EAL3) - methodically tested and checked (chapter 11.5)

"Objectives

EAL3 permits a conscientious developer to gain maximum assurance from positive security engineering at the design stage without substantial alteration of existing sound development practices.

EAL3 is applicable in those circumstances where developers or users require a moderate level of independently assured security, and require a thorough investigation of the TOE and its development without substantial re-engineering."

Evaluation assurance level 4 (EAL4) - methodically designed, tested, and reviewed (chapter 11.6)

"Objectives

EAL4 permits a developer to gain maximum assurance from positive security engineering based on good commercial development practices which, though rigorous, do not require substantial specialist knowledge, skills, and other resources. EAL4 is the highest level at which it is likely to be economically feasible to retrofit to an existing product line.

EAL4 is therefore applicable in those circumstances where developers or users require a moderate to high level of independently assured security in conventional commodity TOEs and are prepared to incur additional security-specific engineering costs."

Evaluation assurance level 5 (EAL5) - semiformally designed and tested (chapter 11.7)

"Objectives

EAL5 permits a developer to gain maximum assurance from security engineering based upon rigorous commercial development practices supported by moderate application of specialist security engineering techniques. Such a TOE will probably be designed and developed with the intent of achieving EAL5 assurance. It is likely that the additional costs attributable to the EAL5 requirements, relative to rigorous development without the application of specialised techniques, will not be large.

EAL5 is therefore applicable in those circumstances where developers or users require a high level of independently assured security in a planned development and require a rigorous development approach without incurring unreasonable costs attributable to specialist security engineering techniques."

Evaluation assurance level 6 (EAL6) - semiformally verified design and tested (chapter 11.8)

"Objectives

EAL6 permits developers to gain high assurance from application of security engineering techniques to a rigorous development environment in order to produce a premium TOE for protecting high value assets against significant risks.

EAL6 is therefore applicable to the development of security TOEs for application in high risk situations where the value of the protected assets justifies the additional costs."

Evaluation assurance level 7 (EAL7) - formally verified design and tested (chapter 11.9)

"Objectives

EAL7 is applicable to the development of security TOEs for application in extremely high risk situations and/or where the high value of the assets justifies the higher costs. Practical application of EAL7 is currently limited to TOEs with tightly focused security functionality that is amenable to extensive formal analysis."

Strength of TOE security functions (AVA_SOF) (chapter 19.3)

"Objectives

Even if a TOE security function cannot be bypassed, deactivated, or corrupted, it may still be possible to defeat it because there is a vulnerability in the concept of its underlying security mechanisms. For those functions a qualification of their security behaviour can be made using the results of a quantitative or statistical analysis of the security behaviour of these mechanisms and the effort required to overcome them. The qualification is made in the form of a strength of TOE security function claim."

Vulnerability analysis (AVA_VLA) (chapter 19.4)

"Objectives

Vulnerability analysis is an assessment to determine whether vulnerabilities identified, during the evaluation of the construction and anticipated operation of the TOE or by other methods (e.g. by flaw hypotheses), could allow users to violate the TSP.

Vulnerability analysis deals with the threats that a user will be able to discover flaws that will allow unauthorised access to resources (e.g. data), allow the ability to interfere with or alter the TSF, or interfere with the authorised capabilities of other users."

"Application notes

A vulnerability analysis is performed by the developer in order to ascertain the presence of security vulnerabilities, and should consider at least the contents of all the TOE deliverables including the ST for the targeted evaluation assurance level. The developer is required to document the disposition of identified vulnerabilities to allow the evaluator to make use of that information if it is found useful as a support for the evaluator's independent vulnerability analysis."

"Independent vulnerability analysis goes beyond the vulnerabilities identified by the developer. The main intent of the evaluator analysis is to determine that the TOE is resistant to penetration attacks performed by an attacker possessing a low (for AVA_VLA.2 Independent vulnerability analysis), moderate (for AVA_VLA.3 Moderately resistant) or high (for AVA_VLA.4 Highly resistant) attack potential."

D Annexes

List of annexes of this certification report

Annex A: Security Target provided within a separate document.

Annex B: Evaluation results regarding development

and production environment

37

This page is intentionally left blank.

Annex B of Certification Report BSI-DSZ-CC-0624-2009

Evaluation results regarding development and production environment



The IT product Samsung S3CC9LC 16-bit RISC Microcontroller for Smart Card, Revision 9 with optional secure RSA 3.7S and ECC 2.4S Libraries including specific IC Dedicated Software (Target of Evaluation, TOE) has been evaluated at an approved evaluation facility using the Common Methodology for IT Security Evaluation, Version 2.3 extended by advice of the Certification Body for components beyond EAL 4 and guidance specific for the technology of the product for conformance to the Common Criteria for IT Security Evaluation (CC), Version 2.3 (ISO/IEC 15408:2005).

As a result of the TOE certification, dated 29 January 2010, the following results regarding the development and production environment apply. The Common Criteria Security Assurance Requirements

- ACM Configuration management (i.e. ACM_AUT.1, ACM_CAP.4, ACM_SCP.3),
- ADO Delivery and operation (i.e. ADO_DEL.2, ADO_IGS.1) and
- ALC Life cycle support (i.e. ALC_DVS.2, ALC_LCD.2, ALC_TAT.2),

are fulfilled for the development and production sites of the TOE listed below:

Site	Address	Function
Giheung Plant	Samsung Electronics. Co., Ltd. San24, Nongseo-	Development, Production
	dong, Giheung-gu, Yongin-City, Gyeonggido , 449-711, Korea	(Wafer Fab)
Hwasung Plant	Samsung Electronics. Co., Ltd. San #16, Banwol-Ri,	Development
	Hwasung-Eup, Gyeonggi-Do, 445-701, Korea	(Server room, Mask data preparation)
Onyang Plant I	Samsung Electronics. Co., Ltd., San #74, Buksoo-Ri, Baebang-Myun, Asan-City, Chungcheongnam-Do,	Production
	449-711, Korea	(Warehouse/Delivery)
Cheonan Plant	PKL Co., Ltd. Plant, 493-3 Sungsung-Dong,	Production
(PKL)	Cheonan-City, Choongcheongnam-Do, 330-300, Korea	(Mask House)
Asan Plant	HANAMICRON Co., Ltd., #95-1, Wonnam-Li,	Production
(Hanamicron) Umbong-Myeon, Asan-City, Choongcheongnam-Do, 449-711, Korea		(Grinding, Sawing)
Onyang Plant II		Production
	Baebang-Myun, Asan-City, Chungcheongnam-Do, 449-711, Korea	(Grinding, Sawing)
Shanghai Plant I	CHANGFENG Co., Ltd., No. 818 Jin Yu Road, Jin	Production
(ChangFeng) Qiao Export Processing Zone Pudong, Shanghai, China		(Sawing, COB Assembly)
Shanghai Plant II (StatsChippac)	STATSCHIPPAC Co., Ltd., 188 Huaxu Road, Qingpu District, 201702 Shanghai, China	Production

Site	Address	Function
		(Grinding)
	Warehouse No. 88 Morden Road Suzhou Industrial	Production (Warehouse/Delivery)
	lin li Hu Road Suzhou Industrial Park Suzhou	Production (Grinding, Sawing, COB Assembly)

Table 4: Identification of Sites

For the sites listed above, the requirements have been specifically applied in accordance with the Security Target [6]). The evaluators verified, that the Threats, Security Objectives and Requirements for the TOE life cycle phases up to delivery (as stated in the Security Target [6] and [9]) are fulfilled by the procedures of these sites.